## DURIT® Protect Pro

ULTIMATE MOST USE products form our standard coatings for demanding, daily use of cookware items. These coatings distinguish themselves by an excellent performance in non-stick and durability.

- Versatile system for top level cookware applications
- Ceramic reinforced system
- Excellent scratch and abrasion resistance
- Exceptional non-stick performance



## MOSTUSE

## **DURIT®** Protect Pro

## DURIT® Protect Pro – our Most use product with an outstanding durability

Excellent combination of scratch and abrasion resistance. Very good non-stick properties. Developed for top level cookware.

| Characteristics             | The fact                       |
|-----------------------------|--------------------------------|
| Quality level for consumers | ***                            |
| Basis                       | PTFE                           |
| Number of layers            | 3                              |
| Coating thickness µm [mils] | 35 - 45 [1.38 - 1.77]          |
| Curing temperature °C [°F]  | 420 [788]                      |
| Service temperature °C [°F] | 250 [482]                      |
| Color variety               | various color options feasible |
| Performance profile         |                                |
| Scratch resistance          | ****                           |
| Abrasion (BS)               | ****                           |
| Non-stick (LGA)             | ***                            |
| Non-stick (LGA & milk)      | ***                            |
| Corrosion resistance        | ***                            |
| Substrate                   |                                |
| Pressed / forged alu        | <b>**</b>                      |
| Cast alu                    | <b>**</b>                      |
| Stainless steel             | <b>**</b>                      |

DURIT® Protect Pro is a three-layer non-stick coating with ceramic reinforcement for highest demands. The product is tailored for the use in top level cookware. Due to an excellent combination of scratch- and abrasion resistance with best non-stick, it is the system of choice.



- ① Ceramic reinforced top coat for a long-lasting, maximal non-stick effect and optimum cleanability
- ② Mid coat with strong ceramic reinforcement for best wear resistance and optimum bonding of all layers
- ③ Primer with strong ceramic reinforcement to guarantee optimum adhesion to the substrate and highest durability
- Specially prepared substrate for an optimum adhesion of the coating to the cookware product



ŭ